

## Technical Data Sheet

### Capatue™ SCA-U60M

#### Abstract

**SCA-U60M** is a bifunctional organo-silane possessing a reactive organic ureido group and a hydrolysable inorganic trimethoxysilyl group. The dual nature of its reactivity allows SCA-U60M to bind chemically to both inorganic materials (e.g. glass, metals, fillers) and organic polymers (e.g. thermosets, thermoplastics, elastomers), thus functioning as an adhesion promoter and as a surface modifier. SCA-U60M is amber, transparent and viscous liquid with an alcohol-like odor and soluble in alcohols, ketones, esters or aromatic hydrocarbons.

#### Chemical Name

1-[3-(Trimethoxysilyl)propyl]urea

#### CAS Registry Number

23843-64-3


#### EINECS

245-904-8

#### Molecular Formula

$C_7H_{18}N_2O_4Si$

#### Molecular Structure



#### Molecular Weight

222.32

#### Equivalents

Product	Supplier
Silquest® A-1524	Momentive (formerly OSi Specialties)
GENIOSIL® GF 98	Wacker

#### Typical Properties

--

[Http://www.capatue.com](http://www.capatue.com) E-mail: [info@capatue.com](mailto:info@capatue.com)

Tel: +86-25-8637 1192, 8637 1193 Fax: +86-25-8637 1191 ext. 0

Add: Block E4, Zidong Industry Park, 2 Zidong Road, Maqun Town, Qixia Dist., Nanjing, Jiangsu, China, 210023



Index	Value
Appearance	Amber, transparent and viscous liquid
Density ( $\rho_{20}$ ), g/cm <sup>3</sup>	1.15
Refractive Index ( $n_D^{25}$ )	1.386
Solubility	Soluble in alcohol, ketone, aether, benzene, most aliphatic esters, hydrolysis releases methanol. React with water.

### Applications and Performance

3-Ureidopropyltrimethoxysilane (CAS No. 23843-64-3), silane coupling agent SCA-U60M, is an essential ingredient in the products of many industries. Examples are:

as a size constituent of finish for glass fiber/glass fabric composites;

as an additive to phenolic, furan and melamine resins for foundry resins and abrasives;

as an additive for sealants and adhesives;

as an additive and/or primer for paints and varnishes to improve adhesion to the substrate.

Important product effects that can be achieved through the use of SCA-U60M are: improved mechanical properties: e.g. flexural strength, tensile strength, impact strength, modulus of elasticity;

improved resistance to moisture and corrosion;

higher temperature of deflection under load;

SCA-U60M also helps improve processing properties such as increased filler content. Compare to its ethoxy counterpart, SCA-U60E, SCA-U60M has a faster reaction speed which is sometime very important in quick-drying sealant and coating application.

### Packing

The regular packing of this product is 25kg plastic pail, 200L steel drums and 1000L immediate bulk container.

[Http://www.capatue.com](http://www.capatue.com) E-mail: [info@capatue.com](mailto:info@capatue.com)

Tel: +86-25-8637 1192, 8637 1193 Fax: +86-25-8637 1191 ext. 0

Add: Block E4, Zidong Industry Park, 2 Zidong Road, Maqun Town, Qixia Dist., Nanjing, Jiangsu, China, 210023

### Storage and Shelf Life

Should be stored in dry, cool, ventilated room; keep away from water, moisture, high temperature and fire. This product has a shelf life of at least 12 months if stored in tightly closed original container at room temperature.

If this product is kept beyond the shelf life recommend on the product label, it is not necessarily unusable, but a quality control should be performed on the properties relevant to the application.

### Product Safety and Handling

When considering the use of any Capatue products in a particular application, you should read our latest Material Safety Data Sheets (MSDS) thoroughly for handling instructions, personal protective equipment if necessary, other safety issue and toxicological data as well as for information on proper transportation, storage and use to ensure that the use you intend can be accomplished safely. Our latest Material Safety Data Sheets (MSDS) and other product safety information are available at [www.capatue.com](http://www.capatue.com) or upon request, from our customer service department.

Use of other material in conjunction with Capatue products may require addition precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

**This product is for industry use only; it is neither tested nor represented as suitable for food, medical or pharmaceutical uses.**

### Limited Warranty Information

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Capatue's products are safe, effective, and fully satisfactory for the intended end use.

Suggestions of use shall not be taken as inducements to infringe any patent.

**Capatue's sole warranty is that the product will meet the Capatue sales specifications in effect at the time of shipment.**

**Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.**

**Capatue specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.**

Capatue disclaims liability for any incidental or consequential damages.  
Customer must do enough tests before their regular production to ensure  
that our product is suitable for their specific application.